

GPS/ GLONASS Antenna Module

MODEL: GAM-25GA

Small size and ruggedness, demand of vehicle locating and marine navigation
GPS/ GLONASS antenna that will sustain harsh environment.



- Operation temperature: -30°C to +80°C
- Input Voltage: 2.5V~5.5V
- Frequency range: 1575.42+1.023MHz
- Gain: 29dB Typ.

GAM-25GA is the most compact GPS/GLONASS antenna module currently available on the market, thanks to our cutting-edge technology that makes the device the tiniest possible without sacrificing performance. With comprehensive coverage almost all the way to the horizon, it performs excellently in foliage or urban canyon environment. Featuring diminutive but substantial enclosure plus unparalleled performance, **GAM-25GA** is compatible with almost every GPS/GLONASS receiver model available on the market and provides a perfect alternative for a vast range of GPS applications in the fields of AVL, vehicle navigation, aviation and military.

SPECIFICATIONS:

Specification	
Physical Condition	
Dimension	72.5mm (OD) x 8.5mm (H)
Weight	>30 grams
Environmental Conditions	
Operation temperature	-30°C to +80°C
Storage temperature	-40°C to +100°C
Relative Humidity	40% to 95%
Electrical Specifications	
Input voltage	2.5V~5.5V
Power Consumption	at 2.5V 6.6mA Typ.
	at 3.0V 10.6mA Typ.
	at 4.0V 14.6mA Typ.
	at 5.0V 20.6mA Typ.
Antenna	
Frequency range	1575Mhz & 1596-1610 MHz
Gain at 10° elevation	2 dBi typical
VSWR	1.5 max
Bandwidth	10 MHz min. @S11≤-10 dB, 24MHz typ.

OUTLINE :