

Marine GPS/VHF Antenna

MODEL: GVA-620L

FOR Marine VHF Radio & AIS SYSTEM & Orbcomm



GPS antenna Specifications: GA62

PHYSICAL CONDITION	
Constructions:	Polycarbonate radome, detachable cable/connector for easy mount, rubber-O-ring between top radome and screw base for waterproof
Dimensions:	60mm(Dia.) x 18.5mm(H)
Weight:	65grams (w/o cable & connector).
Color:	Standard in ivory white, other colours available upon request.
Mounting:	Bulkhead mount with 0.8 inch threaded wing nut (standard accessory).
Cable & Connector	
RF cable:	SMA(M) +10 meter RG58 +TNC(M) (standard) other length (optional)
Pulling strength:	6 Kg @ 5sec. molded plastic on connector end for strain relief.
Connector	SMA(F)
Antenna Element	
Center Frequency:	1575.42 MHz +/-1.023 MHz
Polarization:	R.H.C.P. (Right Handed Circular Polarization).
Absolute Gain @ Zenith:	+5 dBi typical.
Gain @ 10° Elevation:	-1 dBi typical.
Axial Ratio:	3 dB max.
Output VSWR:	1.5 max
Output Impedance:	50 ohm
Low Noise Amplifier	
Center Frequency:	1575.42 MHz
Power Gain:	28db +/-4.5db
Bandwidth:	2 MHz min.
Noise Figure:	1.5 min.
Outer Band Attenuation:	20 dB min. @ Fo +/-50 Mhz.
Supply Voltages:	2.5~5.5V DC.

BJTEK Navigation Inc.	2.5V : 6.6mA Typ. 3V: 8.6mA Typ. 4V: 12.6mA Typ. 5V: 16.6mA Typ.	https://www.bjnav.com/
Current Consumption:		
Output Impedance:	50W ohm	
Overall Performance: (antenna element, LNA & coax cable)		
Center Frequency:	1575.42 Mhz.	
Gain:	At 90° vertical to sky 30 ± 4.5dBi (cable loss) Note:1 Mounted on the 60mm x 60mm square ground plane	
Noise Figure:	2.0 max.	
Axial Ratio:	3 dB max.	
Bandwidth:	2MHz min.	
VSWR:	2.0 max.	
Output Impedance:	50W ohm	
Environmental		
Operating Temperature:	-40°C~ +85°C.	
Storage Temperature:	-50°C~ +90°C.	
Relative Humidity:	95% non-condensing.	
Water Resistance:	100% waterproof.	

Marine VHF Antenna Specifications:

	SUS Whip VHF ANTENNA
Fr :	156 ~ 165 Mhz
Gain:	0dB
VSWR	2.0:1
Impedence:	50 ohm
Connector:	SMA(M)
Ground	With FB6 Base mounting
Dimension:	35.2mm
Weight:	46g
Cable :	SMA(SBJ)-10M-TNC(M) or other

* This specification is subject to change without prior notice

Data Updated: OCT.21, 2011

FB6 SUS L- mounting :





